

# PLUGGABLE TERMINAL BLOCK POWER SUPPLY



Parameter	Rated Value	Absolute Maximum				
Input Voltage	100 ~ 240 VAC	90 ~ 264 VAC				
Input Frequency	50/60 Hz	47 ~ 63 Hz				
Input Current (@100-240 VAC)	-	1.0 A				
Inrush Current (@100-240 VAC)	-	80 A				
Output Voltage	24	24 VDC ±5%				
Output Current	0 ~ 1.0 A	-				
Overshoot	-	10%				
Certification	IEC 62368-1:2014 (Second Edition)					
Short-Circuit Protection	√					
Input Protection	Fuse					
HIPOT (Dielectric Withstand Test)	3000 VAC					
MTBF	20000 h					
Weight	172g					
Dimension	L:76*W:44*H:31.3mm					
Input Plug&Part Number	<b>Global</b>	<b>UK</b>	<b>US</b>	<b>CN</b>	<b>AU</b>	<b>EU</b>
	<b>S011054</b>	<b>S011049</b>	<b>S011050</b>	<b>S011051</b>	<b>S011052</b>	<b>S011053</b>
	<i>*Note: The UK plug, US plug, AU plug, and EU plug are all included in Global version.</i>					
Output Connector	Pluggable terminal block, 2-pin, 3.5 mm pitch with lock					
Related Products	EG5120, R5020, R5020-Lite					

