

2-PIN CORD END TERMINAL POWER SUPPLY 24W



| Parameter | Rated Value | Absolute Maximum | | | | | | | | | | | | |
|------------------------------------|--|------------------|---------|---------|---------|----|----|---------|---------|---------|---------|---------|---------|--|
| Input Voltage | 100 ~ 240 VAC | 90 ~ 264 VAC | | | | | | | | | | | | |
| Input Frequency | 50/60 Hz | 47 ~ 63 Hz | | | | | | | | | | | | |
| Input Current (@100-240 VAC) | - | 1.0 A | | | | | | | | | | | | |
| Inrush Current (@100-240 VAC) | - | 80 A | | | | | | | | | | | | |
| Output Voltage | 24 | 24 VDC ± 5% | | | | | | | | | | | | |
| Output Current | 0 ~ 1.0 A | - | | | | | | | | | | | | |
| Overshoot | - | 10% | | | | | | | | | | | | |
| Certification | IEC 62368-1:2014 (Second Edition) | | | | | | | | | | | | | |
| Short-Circuit Protection | √ | | | | | | | | | | | | | |
| Input Protection | Fuse | | | | | | | | | | | | | |
| Hi-POT (Dielectric Withstand Test) | 3000 VAC | | | | | | | | | | | | | |
| MTBF | 20000 h | | | | | | | | | | | | | |
| Weight | 170g | | | | | | | | | | | | | |
| Dimension | L:76*W:44*H:31.3mm | | | | | | | | | | | | | |
| Input Plug&Part Number | <table border="1"> <thead> <tr> <th>Global*</th> <th>UK</th> <th>US</th> <th>CN</th> <th>AU</th> <th>EU</th> </tr> </thead> <tbody> <tr> <td>S012023</td> <td>S012018</td> <td>S012019</td> <td>S012020</td> <td>S012021</td> <td>S012022</td> </tr> </tbody> </table> | Global* | UK | US | CN | AU | EU | S012023 | S012018 | S012019 | S012020 | S012021 | S012022 | |
| Global* | UK | US | CN | AU | EU | | | | | | | | | |
| S012023 | S012018 | S012019 | S012020 | S012021 | S012022 | | | | | | | | | |
| | *Note: The UK plug, US plug, AU plug, and EU plug are all included in Global version. | | | | | | | | | | | | | |
| Output Connector | 2-pin, with cord end terminal | | | | | | | | | | | | | |
| Related Products | EG5120, R5020, R5020-Lite | | | | | | | | | | | | | |

