

PLUGGABLE TERMINAL BLOCK POWER SUPPLY



Parameter	Rated Value	Absolute Maximum												
Input Voltage	100 ~ 240 VAC	90 ~ 264 VAC												
Input Frequency	50/60 Hz	47 ~ 63 Hz												
Input Current (@100 - 240 VAC)	-	0.4A												
Inrush Current (@100 - 240 VAC)	-	60A												
Output Voltage	12 VDC	12VDC ± 5%												
Output Current	0 ~ 1.0A	-												
Overshoot	-	10%												
Certification	IEC 62368 - 1:2014 (Second Edition)													
Short-Circuit Protection	√													
Input Protection	Fuse													
HIPOT (Dielectric Withstand Test)	3000VAC													
MTBF	20000 h													
Input Plug&Part Number	<table border="1"> <thead> <tr> <th>Global*</th> <th>UK</th> <th>US</th> <th>CN</th> <th>AU</th> <th>EU</th> </tr> </thead> <tbody> <tr> <td>S011007</td> <td>S011008</td> <td>S011009</td> <td>S011010</td> <td>S011011</td> <td>S011012</td> </tr> </tbody> </table>	Global*	UK	US	CN	AU	EU	S011007	S011008	S011009	S011010	S011011	S011012	
Global*	UK	US	CN	AU	EU									
S011007	S011008	S011009	S011010	S011011	S011012									
	*Note: The UK plug, US plug, AU plug, and EU plug are all included in Global version.													
Output Connector	Pluggable terminal block, 3-pin, 5.0 mm pitch with lock													
Related Products	R3000													

